

old growth douglas fir – nail edge

Flooring & paneling made from old growth beams reclaimed from Pacific Northwest buildings.



Nailly old ceiling joists create a sharp look for floors or walls

Nail edge flooring is an innovative use for nailly joists reclaimed from old warehouses. Pulling all those nails is difficult work, but it's worth the effort to craft this beautiful flooring and paneling. Simply put it is some of the finest and tightest grain fir around, and paired with the dark holes and black oxide stains it creates a vintage look that tells its own story when you see it. And for something truly unique our paneling is available with a WindWorn™ texture. Reminiscent of barn wood worn down by the elements, WindWorn finish is an extremely affordable and distinctive way to use reclaimed wood.

If nail edge isn't your thing we we've still got you covered. We have tight vertical and mixed grain fir that calls to mind a classic Old Portland bungalow, or if you're looking for something rustic we can supply a weathered, original beam face that is precision milled to install beautifully.

fast facts: old growth douglas fir – nail edge

available as:

Solid Flooring
Solid Paneling
WindWorn™ Textured Paneling

flooring dimensions:

Thickness ¾"
Face Width 3"
Random Lengths: 4-10'

character options:

Nail Edge (lots of nail holes and oxide)
Mixed Grain
Vertical Grain
Rustic (original beam face)

hardness:

660-710 (Janka scale).

environment:

100% FSC® certified, post-consumer reclaimed from sustainable sources. Choosing this product reduces demand for new lumber and saves trees.

made in the pacific northwest:

Reclaimed and manufactured in the Pacific Northwest to keep jobs, resources & money where they should be, local!



877-909-WOOD
viridianwood.com

old growth douglas fir – nail edge

flooring & paneling specification



description	Tight grain douglas fir with exceptionally tight mixed grain and an occasional nail hole to let you know it is reclaimed. Available in multiple widths or mix widths to create additional interest.
source	Old growth beams reclaimed from Pacific Northwest building deconstruction and remodeling.
net dimensions	thickness: ¾" face width: 3" lengths: 4-10'
millwork	Tongue & groove, square edge, mill run (end cut at time of installation).
species	<i>Pseudotsuga menziesii</i>
hardness	660-710 (Janka scale).
grade	All material is C&Btr grade and kiln dried.
character	Color: Rich honey color that subtly darkens over time. This natural process, called patina, will add to the beauty and character of your wood. Color sorting is subjective and not guaranteed. Nail Edge flooring & paneling was previously ceiling joists and contains very tight mixed grain with many random nail holes, black oxide staining, heartwood and sapwood, occasional tight knots, minor pitch pockets and very infrequent non-structural checks up to 1/16".
finish	Unfinished unless specified (factory finish available for all paneling except Rustic face). Paneling available with WindWorn™ textured wood finish (reminiscent of barn wood worn down by the elements), see WindWorn specification sheet for details.
shipping	All material is FOB Portland or Seattle, please call for details (factory finished FOB Seattle). We can coordinate local or national delivery. Material is bundle packaged and bundles are packed into units 4' wide x up to 10' long (most 6' or less). Estimated ship weight: 2¼ pounds per square foot.
installation	Store, handle and install per National Wood Flooring Association (NWFA) guidelines available at viridianwood.com.
LEED	MR 3: Materials Reuse, MR 4: Recycled Content, MR 5: Regional Materials (Seattle, WA), MR 7: Certified Wood
	Certified recycled 100% (post consumer reclaimed) by Forest Stewardship Council (FSC). Cert No SW-COC-001962.

