

Jakarta Market Blend – Tropical Mix Paneling

Locally reclaimed in Portland, Oregon from exotic hardwood shipping crates



Jakarta Market Blend – Tropical Mix Paneling

Jakarta Market Blend is a mix of dense hardwoods from the tropical lowlands of Asia, one of the most biologically diverse places on Earth. This wood arrives in Portland, Oregon as transpacific shipping crates. Its proven to withstand punishing conditions of heavy cargoes and rough seas, yet just below the surface of its rugged exterior are gorgeous hardwoods bursting with personality. We reclaim this wood ourselves, to rescue it and give it new life in Jakarta Market Blend. It's extremely versatile – available in many colors and options, and well suited to residential and commercial applications. Each one-of-a-kind board has its own unique character and amazing story that will speak to you.

Fast Facts: Jakarta Market Blend – Tropical Mix Paneling

Available as:

Solid Paneling
Solid Flooring
Tabletops
Prefinished

Paneling Dimensions:

Thickness 5/8"
Face Width 2 1/2"
Random Lengths: 1-6 1/2'

Other Color Options:

Tropical Mix (shown)
Dark Sort
Light Sort
Rustic (original face)

Hardness:

1100-3500 (Janka scale). Suitable for high traffic & commercial applications.

Environment:

100% FSC certified, post-consumer reclaimed from sustainable sources. Choosing this product reduces demand for new lumber and saves trees.

Made in Oregon:

Reclaimed in Portland and manufactured in Oregon to keep jobs, resources and money where they should be, local!



877-909-WOOD
viridianwood.com

jakarta market blend – tropical mix paneling

specification



description

A rich mix of dense tropical hardwoods rescued from transpacific shipping. Jakarta Market Blend – Tropical Mix brings together a wide spectrum of our exotic hardwoods to create a unique, custom look.

source

Locally reclaimed in Portland, Oregon from exotic hardwood shipping crates. Due to the difficulty in reclaiming the material the wood was previously discarded or burned. Viridian pioneered a process to divert the material from landfills, separate the highest quality wood and give it new life in our flooring and paneling.

net dimensions

thickness: 5/8" face width: 2 1/2" lengths: 1-6 1/2' (average 4'+)

millwork

Tongue & groove, square edge (microbevel also available), mill run (end cut at time of installation).

species

Mempening, Bintangor, Agoho, Rengas, Mertas, Nayotah, Simpoh, Bitis, Thitka and others (list available upon request). The variability in species is consistent across lots so recurring orders will have a similar random look and feel.

hardness

1100-3500 (Janka scale). Suitable for high traffic & commercial applications.

character

Color: Unlimited color variation is inherent to product. Contains all hues of red, brown, tan, gold, graphite and ivory among others. Exposure to light may cause subtle color changes over time. This natural process, called patina, will add to the beauty and character of your wood. Color sorting is subjective and not guaranteed.

May contain: unlimited grain combinations including flat, quarter, rift, and plain sawn; heartwood and sapwood; oxide staining and discoloration from prior use; infrequent tight knots, nail holes and some insect holes (all material is kiln dried); very infrequent non-structural checks up to 1/16"

Other notes: Milling removes virtually all previous marks; occasional pieces show saw marks and previous wear patterns.

finish

Unfinished unless specified (factory finish available for paneling).

shipping

All material is FOB Portland (factory finished FOB Seattle). We can coordinate local or national delivery.

Material is bundle packaged and bundles are packed into units 4' wide x up to 6 1/2' long.

Estimated ship weight: 3 1/2 pounds per square foot.

installation

Store, handle and install per National Wood Flooring Association (NWFA) guidelines available at viridianwood.com.

LEED

MR 3: Materials Reuse, MR 4: Recycled Content, MR 5: Regional Materials (Portland, OR), MR 7: Certified Wood

Certified recycled 100% (post consumer reclaimed) by Forest Stewardship Council (FSC). Cert No SW-COC-001962.

