

WindWorn™ Textured Reclaimed Paneling

Distinctive paneling made from old growth beams and transpacific shipping crates.



Our customers love the genuine weathered exterior of our Old Growth Douglas Fir beams, but finding enough original beam face that is suitable for paneling is hard to come by. So Viridian set out to create the textured reclaimed wood look that people crave using more affordable materials and processes. The result is our WindWorn line of textured wood paneling.

Reminiscent of barn wood that has been worn down by the elements, we've taken our reclaimed Reclaimed Douglas Fir and Siberian Spruce and given them a natural looking, raked texture. The vertically sculpted lines provide a mesmerizing contrast that blurs the lines between modern and rustic. Leave it clear for a fresh, contemporary look, or if you want to capture that rugged, old-world look you can apply a simple wiping stain to give it an aged patina.

WindWorn textures are made to order...We can keep it simple with a raked texture, or we can add bandsaw and circle saw marks to create more sculpted interest. Getting just the right combination of texture and function is an art...all wood is precision milled for tight-fitting installation, and then we enhance the grain pattern using proprietary techniques. The resulting texture is free from splinters and catches and durable enough for commercial environments.

Fast Facts: WindWorn Textured Reclaimed Paneling

available as:

Solid Flooring
Solid Paneling
WindWorn™ Textured Paneling

flooring dimensions:

Thickness ¾"
Face Width 3"
Random Lengths: 4-10'

character options:

Nail Edge (lots of nail holes and oxide)
Mixed Grain
Vertical Grain
Rustic (original beam face)

hardness:

660-710 (Janka scale).

environment:

100% FSC® certified, post-consumer reclaimed from sustainable sources. Choosing this product reduces demand for new lumber and saves trees.

made in the pacific northwest:

Reclaimed and manufactured in the Pacific Northwest to keep jobs, resources & money where they should be, local!



877-909-WOOD
viridianwood.com

old growth douglas fir – nail edge

flooring & paneling specification



description	Tight grain douglas fir with exceptionally tight mixed grain and an occasional nail hole to let you know it is reclaimed. Available in multiple widths or mix widths to create additional interest.
source	Old growth beams reclaimed from Pacific Northwest building deconstruction and remodeling.
net dimensions	thickness: ¾" face width: 3" lengths: 4-10'
millwork	Tongue & groove, square edge, mill run (end cut at time of installation).
species	<i>Pseudotsuga menziesii</i>
hardness	660-710 (Janka scale).
grade	All material is C&Btr grade and kiln dried.
character	Color: Rich honey color that subtly darkens over time. This natural process, called patina, will add to the beauty and character of your wood. Color sorting is subjective and not guaranteed. Nail Edge flooring & paneling was previously ceiling joists and contains very tight mixed grain with many random nail holes, black oxide staining, heartwood and sapwood, occasional tight knots, minor pitch pockets and very infrequent non-structural checks up to 1/16".
finish	Unfinished unless specified (factory finish available for all paneling except Rustic face). Paneling available with WindWorn™ textured wood finish (reminiscent of barn wood worn down by the elements), see WindWorn specification sheet for details.
shipping	All material is FOB Portland or Seattle, please call for details (factory finished FOB Seattle). We can coordinate local or national delivery. Material is bundle packaged and bundles are packed into units 4' wide x up to 10' long (most 6' or less). Estimated ship weight: 2¼ pounds per square foot.
installation	Store, handle and install per National Wood Flooring Association (NWFA) guidelines available at viridianwood.com.
LEED	MR 3: Materials Reuse, MR 4: Recycled Content, MR 5: Regional Materials (Seattle, WA), MR 7: Certified Wood
	Certified recycled 100% (post consumer reclaimed) by Forest Stewardship Council (FSC). Cert No SW-COC-001962.

